

Stanley Access Technologies ICU/CCU 7000 Door Series



DESIGNED TO MEET THE SPECIFIC NEEDS OF HOSPITAL INTENSIVE AND CARDIAC CARE UNITS (ICU/CCU)

- Broad glass panels provide unobstructed view to patients.
- The ICU 7500 Series Telescopic provides greater clear door opening for a given rough opening.
- Patients remain undisturbed by nearby activity, or other intrusions.
- Provides easy, flexible access to the patient area.
- The 7200 Series allows for a trackless threshold feature with the ability to breakout the SX panel at any point.
- Smoke and Draft Controls now available on standard 2-panel and 3-panel ICU/CCU Door systems.
- Designed to meet UL®1784 and NFPA105.
- · Positive latching available.

Stanley Access Technologies - the safest, most cost effective solutions available today.

Stanley Access Technologies


65 Scott Swamp Road Farmington, CT 06032 www.stanleyaccess.com




Stanley Access Technologies ICU/CCU 7000 Door Series


7000 ICU SERIES


PACKAGE WIDTH CLEAR EMERGENCY BREAKOUT SIDELIGHT AND SLIDING 2 Panel






7200 ICU SERIES






7500 ICU SERIES TELESCOPING





6 Panel (Trackless)



3 Panel (Trackless)

Door Packages are Manufactured To Fit Your Job Requirements

Standard Height for all ICU/CCU Entrances is 88 inches

Width Ranges are as Follows:


- 7000 ICU Series Single Slide: 84" to 108" Wide
- 7000TL (Trackless) ICU Series Single Slide: 84" to 102" Wide
- 7500/7500TL (Trackless) ICU Series Telescopic: 72" to 160" Wide
- 7500TL (Trackless FBO) ICU Series Telescopic: 74" to 142" Wide

Note: Not all products depicted, please refer to website for complete product line.

7000 Product Line Features and Benefits

	7000	7000 TL	<i>7</i> 200	<i>7500</i>	7500 TL	7500 TLFBC
Panels	2, 3 ¹ , 4	2, 3 ¹ , 4	2,4	3, 6	3, 6	3, 6
w/Track						
Trackless		0	0			
Full Breakout		2				2
Fixed Sidelight						
Positive Latch ³	0	0	0			
Smoke & Draft ⁴	2 Panel	2 Panel	2 Panel	3 Panel	3 Panel	3 Panel

- 1. 3 Panel model incorporates additional fixed or breakout side light.
- 2. Trackless model must be in full open position prior to breakout.
- 3. Positive latch option available on all models; included with Smoke and Draft Control.
- 4. Smoke and Draft packages shall not exceed 168" (W) x 120" (H).
- 5. Capable of supporting glazing from 1/4" to 1".



Slide/Swing model also available, for information on 7600 ICU Series refer to SAT sell sheet AT-2241

For Service, Call Stanley Toll Free: 1-800-7-ACCESS (1-800-722-2377)

Stanley Access Technologies

65 Scott Swamp Road Farmington, CT 06032 www.stanlevaccess.com